



Body Style: Sport-utility vehicle

Layout: Longitudinal front engine, 2WD or 4WD

Seat Layout: 2/3

EPA Vehicle Class:
Multi-purpose vehicle

Assembly: Toledo North
Assembly Plant, Toledo, OH

2010 JEEP LIBERTY GIVES OWNERS PERSONAL FREEDOM AND CAPABILITY THAT ONLY COMES FROM JEEP

The 2010 Jeep Liberty gives customers an “only in a Jeep” open-air experience with its industry-exclusive Sky Slider full-length open canvas roof.

New for 2010 is interactive Decel Fuel Shut Off (iDFS0). Standard on all models, iDFS0 turns off fuel during vehicle deceleration, which improves fuel economy without any noticeable changes in engine performance. In addition, the new standard fuel-saver indicator displays when the vehicle is driven in a fuel-efficient manner.

Other standard features for 2010 include front-row Active Head Restraints, premium seat trim with stain-repel seat fabric, air filtration system and larger floor mats.

The 2010 Jeep Liberty features the industry-exclusive Sky Slider full-length open canvas roof. The Sky Slider roof may be moved to several positions, including full forward, full rear or partially open to any position in between with a convenient express one-touch switch.

A 3.7-liter V-6 engine is standard on all Jeep Liberty models. The 3.7-liter engine produces 210 horsepower (157 kW) @ 5,200 rpm and 235 lb.-ft. (319 N•m) of torque @ 4,000 rpm.

The 2010 Jeep Liberty offers two four-wheel-drive systems. Command-Trac II® is a part-time four-wheel-drive system, which is the standard 4WD configuration. Command-Trac II operates in 2WD, 4WD Lock, 4 WD Low and Neutral.

The optional Selec-Trac II® is a full-time, active on-demand four-wheel-drive system. Select-Trac II operates in 2WD, 4WD Auto, 4WD Low and Neutral.

The 2WD position is for normal driving and achieves optimal fuel economy as the front driveshaft is disengaged from the transfer case, and power is directed to rear wheels.

The Command-Trac II® 4WD Lock position locks the front and rear driveshaft together and forces front and rear wheels to rotate at the same speed. These positions are intended for loose or slippery road surfaces only.

In the Select-Trac II 4WD Auto position, the transfer case anticipates and prevents wheel slip. It is ideal for a range of road settings including dry pavement conditions not typically suited for conventional part-time four-wheel-drive systems.

4WD Low is for true off-road conditions and is engaged at speeds of 0-2 mph. Front and rear driveshafts are locked together and a second gearset multiplies torque which provides traditional Jeep capability. 4WD Low is suitable for speeds less than 30 mph.

Vehicles equipped with Jeep Liberty's four-wheel-drive systems are Trail Rated®.

MODEL / POWERTRAIN

MODEL	ENGINE	TRANSMISSION
	3.7L V-6	4-SPEED AUTO (42RLE)
Sport	S	S
Limited	S	S

NEW FOR 2010

- Interactive Decel Fuel Shut Off (iDFS0)
- Fuel-Saver with “ECO” lamp indicator in cluster
- Standard front-row Active Head Restraints
- Uconnect™ Phone (Limited model)
- Front-passenger Express-up power window (Limited model)
- Power heated manual folding mirrors (Sport model)
- Standard air filtration system
- Standard premium seat trim with stain-repel seat fabric and front-passenger fold-flat seat
- Leather interior seat trim (Limited model)
- Heated front seats (Limited model)
- Power driver and passenger leather seats with manual lumbar control (Limited model)
- Larger floor mats standard
- Light Sandstone Metallic replaces Light Graystone exterior color

SAFETY AND SECURITY


More than 25 advanced safety and security features including:

- Advanced multi-stage air bags
- Anti-lock Brake System (ABS)
- Brake Assist
- Electronic-roll Mitigation (ERM)
- Electronic Stability Control (ESC)
- Hill-descent Control (HDC) (4WD only)
- Hill-start Assist (HSA)
- ParkSense® rear-park assist system
- Supplemental side-curtain air bags

FUEL ECONOMY (city/hwy)

3.7L SOHC V-6
16/22 – 2WD
15/21 – 4WD

DIMENSIONS, IN. (MM)



O.A. Width: 73.1 (1856.9) **Curb Wt. lb.(kg):**
2WD: 4,076 (1850)
Track, Front: 61.0 (1549.4) **4WD:** 4,290 (1947)

Track, Rear: 61.0 (1549.4)

^(a) With roofrack

2010 JEEP® LIBERTY AT A GLANCE

2010 Jeep® Liberty remains true to its legendary 4x4 heritage

- Choice of two 4x4 systems
- Selec-Trac II® four-wheel-drive system – Full-time, shift-on-the-fly, active four-wheel drive system offers customers the benefit of a fully electronic two-speed active transfer case and Brake-traction control system (BTCS). It instantly anticipates wheel slip and redirects torque accordingly, which is ideal for off-roading or when driving in inclement weather
- Command-Trac® II four-wheel-drive system – Part-time, shift-on-the-fly, fully electronic system provides four-wheel-drive capability delivered through a two-speed transfer case for use on slippery or loose surfaces (snow, mud or sand)
- Hill-descent Control (HDC) – Allows a smooth and controlled hill descent on rough or slippery terrain without the driver needing to touch the brake pedal
- Hill-start Assist (HSA) – Assists drivers when starting a vehicle from a stop on a hill by maintaining the level of brake pressure applied for a short period of time after the driver's foot is removed from the brake pedal
- Neutral position permits flat towing a Liberty behind a motor home. A push-pin button is provided to shift the transfer case into Neutral (4WD only)
- Jeep Trail Rated capability

On-road ride, handling, performance and fuel economy

- Independent front suspension, five-link rear suspension and rack-and-pinion steering for improved on-road ride and handling
- 3.7-liter SOHC V-6 engine delivers 210 horsepower (157 kW) @ 5,200 rpm and 235 lb.-ft. (319 N•m) of torque @ 4,000 rpm and improved fuel economy
- Interactive Decel Fuel Shut Off (iDFSO)
- Fuel-Saver with "ECO" lamp indicator in cluster
- With optional Trailer-tow package, Trailer-sway Control (TSC) helps reduce trailer sway and improves handling in adverse towing conditions caused by crosswinds and traffic
- Unsurpassed 5,000-lb. trailer-towing capability (when properly equipped with Trailer-tow package)
- Standard safety and security features include Supplemental Side-curtain Air Bags, Electronic Stability Control (ESC), Electronic-roll Mitigation (ERM) and Brake Assist, Anti-lock Brake System (ABS), Brake-traction control system (BTCS) and Tire-pressure Monitoring (TPM)

Classic Jeep exterior styling with functional interior space

- Rugged appearance, flatter hood, taller seven-slot grille with encased round headlamps
- Functional interior space – standard fold-flat front-passenger seat, fold-flat second-row passenger seats and a reversible cargo floor
- Limited model features bright-side roof rails, bright front grille, fog lamps and interior details
- Sport model features standard body-color fascias and wheel flares

Innovative premium amenities (optional)

- Industry-exclusive Sky Slider™ full-open roof available on Sport and Limited models is four times larger than a conventional sun roof
- Uconnect™ Navigation
- Uconnect Phone
- Eight premium audio speakers and 368-watt amplifier
- Other options include power sun roof, 18-inch chrome clad aluminum wheels, automatic temperature control, ParkSense® rear-park assist system and remote start

2010 JEEP® LIBERTY SPECIFICATIONS

All dimensions are in inches (millimeters) at curb weight and with standard wheels and tires unless otherwise noted.

GENERAL INFORMATION

Body Style	Sport-utility vehicle
Construction	Steel uniframe
Assembly Plant	Toledo, Ohio
EPA Vehicle Class	Multi-purpose vehicle

ENGINE: 3.7-LITER SOHC V-6

Availability	Standard
Type and Description	90-degree V-6, liquid-cooled with balance shaft
Displacement	225.8 cu. in. (3700 cu. cm)
Bore x Stroke	3.66 x 3.57 (93.0 x 90.8)
Valve System	Chain-driven, SOHC, 12 valves, with hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Cast-iron block, compacted graphite bedplate, aluminum alloy heads, balance shaft
Compression Ratio	9.7:1
Power (SAE net)	210 hp (157 kW) @ 5,200 rpm (56.8hp/L)
Torque (SAE net)	235 lb.-ft. (319 N•m) @ 4,000 rpm
Max. Engine Speed	6,000 rpm, electronically limited
Fuel Requirement	Regular unleaded, 87 octane (R+M)/2
Oil Capacity	5.0 qt. (4.7L)
Coolant Capacity	14.0 qt. (13.25L)
Emission Controls	Two mini-oxidation 3-way catalytic converters; four heated oxygen sensors; EGR and internal engine features ^(a)
Max. Gross Trailer Weight	
Automatic with Trailer-tow package	5,000 lbs. (2250 kg)
Estimated 2010 EPA Fuel Economy –mpg (City/Hwy)	16/22 – 2WD with Automatic Transmission 15/21 – 4WD with Automatic Transmission

^(a) Meets ULEV II emission standard in all 50 states.

TRANSMISSION: 42RLE—AUTOMATIC FOUR-SPEED OVERDRIVE

Availability	Standard
Description	Adaptive electronic control and electronically modulated torque converter clutch
Gear Ratios	
1st	2.84
2nd	1.57
3rd	1.0
4th	0.69
Reverse	2.21
Axle	3.73
Overall Top-gear	2.57

2010 JEEP® LIBERTY SPECIFICATIONS

TRANSFER CASE: MP1522 COMMAND-TRAC II®

Availability	Standard on 4WD models
Type	Part-time, electronic shift
Operating Modes	2WD, 4WD Lock, 4WD Low, Neutral
Center Differential Type	None
Torque Split, F/R	50/50
Low-range Ratio	2.72:1

TRANSFER CASE: MP3022 SELEC-TRAC II®

Availability	Optional on 4WD models
Type	Full-time active on-demand, electronic shift
Operating Modes	2WD, 4WD Auto, 4WD Low, Neutral
Center Differential Type	None
Torque Split, F/R	42/58
Low-range Ratio	2.72:1

AXLE RATIOS

3.7-liter V-6 Engine Auto	3.73:1
---------------------------	--------

ELECTRICAL SYSTEM

Alternator	140-amp
Battery	600-amp, maintenance-free

DIMENSIONS AND CAPACITIES^(a)

Wheelbase	106.1 (2694.4)
Track, Front	61.0 (1549.4)
Track, Rear	61.0 (1549.4)
Overall Length (NAFTA vehicles)	176.1 (4473.3)
Overall Width	73.1 (1856.9)
Overall Height (with roof rack)	71.3 (1810.4)
Load-Floor Height	34.1 (866.3)
Sill-Step Height	20.2 (514.0)
Ground Clearances (4WD with P235/65R17 tires)	
Chassis	9.5 (240.7)
Fuel Tank	9.5 (240.0)
Front Axle	7.8 (198.0)
Rear Axle	8.1 (205.2)
Approach Angle, (with air dam)	28.7°
Breakover Angle	21.5°
Departure Angle	30.1°
Frontal Area	30.21
Aero CdA	12.0
Aero Cd	0.394
Fuel-tank Capacity	19.5 gal. (73.8L)

2010 JEEP® LIBERTY SPECIFICATIONS

Maximum occupants and cargo weight, 16-inch tires only, lbs. (kg)	950 (431 kg)
Maximum occupants and cargo weight, lbs. (kg)	1,150 (522 kg)
All models without Trailer-tow Group and equipped with aftermarket Class II type hitch	2,000 (907)
3.7L engine automatic transmission with Trailer-tow package (Class III)	5,000 (2268)
Curb Weight, lbs. (kg)	
3.7-liter 2WD	4,076 (1850)
3.7-liter 4WD	4,290 (1947)
Weight Distribution, 4x4, F/R	44/56

^(a) All dimensions measured with two passengers.

ACCOMMODATIONS

Seating Capacity—F/R	2/3
Front Row	
Head Room without Sun Roof	40.4 (1025.1)
Head Room with Sun Roof	38.2 (971.0)
Leg Room	40.8 (1035.8)
Shoulder Room	57.1 (1450.4)
Hip Room	52.7 (1338.1)
Seat Travel	9.0 (229.1)
Recliner Range	6.6° to 51.6°
SAE Volume (standard roof)	54.47 cu. ft.
Second Row	
Head Room	40.8 (1036.2)
Leg Room	38.2 (969.7)
Knee Clearance	2.0 (49.7)
Shoulder Room	56.6 (1436.7)
Hip Room	52.6 (1337.0)
Recliner Range	21.5° to 33.5°
SAE Volume (standard roof)	51.06 cu. ft.
Cargo Access	
Liftover Height	34.1 (866.4)
Maximum Cargo Width at Liftgate Opening	44.2 (1122.9)
Minimum Cargo Width at Liftgate Opening	41.2 (1046.4)
Maximum Cargo Height at Liftgate Opening	29.6 (751.0)
Minimum Cargo Height at Liftgate Opening	29.4 (746.0)
Distance Between Wheelhouse Interior Trim	41.4 (1050.9)
SAE Cargo Volume	
Behind Rear Seat	25.2 cu. ft. (0.7 cu. m)
Behind Front-row Seats with Rear Seats Folded	60.9 cu. ft. (1.7 cu. m)

2010 JEEP® LIBERTY SPECIFICATIONS

BODY AND CHASSIS

Layout	Longitudinal front engine, rear-wheel drive or four-wheel drive
Construction	Steel uniframe

SUSPENSION

Front	Upper and lower “A” arms, coil springs, low-pressure gas-charged shock absorbers and stabilizer bar
Rear	Live axle, upper and lower trailing arms, track bar, coil springs, low-pressure gas-charged shock absorbers and stabilizer bar

STEERING

Type	Power rack-and-pinion
Overall Ratio	17.36:1
Turning Diameter (curb-to-curb)	35.5 ft. (10.83 m)
Steering Turns (lock-to-lock)	3.42

BRAKES

Front	
Size and Type	11.9 x 1.1 (302 x 28) vented rotor with 2.6 (66) single-piston floating caliper
Swept Area (per caliper)	110.1 sq. in. (710.6 sq. cm)
Rear	
Size and Type	12.44 x 0.47 (316 x 12) solid rotor with 1.9 (48) single-piston floating caliper
Swept Area (per caliper)	103.5 sq. in. (668 sq. cm)
Power-assist Type	8 x 9 (204 x 230) tandem diaphragm, vacuum assist
Four-wheel Anti-lock Brake System (ABS)	Standard
Electronic Stability Control (ESC)	Standard
Parking Brake Type	Rear brake drum-in-hat

2010 JEEP® LIBERTY SPECIFICATIONS

WHEELS

Availability	Standard on Liberty Sport
Type and Material	Painted Sparkle Silver Cast Aluminum
Size	16-in. x 7-in.
Availability	Standard on Liberty Limited
Type and Material	Painted Tech Silver Cast Aluminum
Size	17-in. x 7-in.
Availability	Available on Liberty Limited
Type and Material	Chrome-clad cast aluminum
Size	18-in. x 7-in.

TIRES

Availability	Standard on Liberty Sport
Size and Type	P225/75R16 BSW, all-season
Mfr. and Model	Goodyear Wrangler ST
Revs per Mile (km)	715 (444)
Availability	Standard on Liberty Limited
Size and Type	P235/65R17 BSW, all-season
Mfr. and Model	Goodyear Wrangler HP
Revs per Mile (km)	723 (449)
Availability	Available on Liberty Sport
Size and Type	P225/75R16 OWL, all-season
Mfr. and Model	Goodyear Wrangler ST
Revs per Mile (km)	715 (444)
Availability	Available on Liberty Sport
Size and Type	P235/70R16 OWL, all-season, all-terrain
Mfr. and Model	Goodyear Wrangler SRA
Revs per Mile (km)	727 (452)
Availability	Available on Liberty Limited
Size and Type	P235/60R18 BSW, all-season
Mfr. and Model	Goodyear Fortera HL
Revs per Mile (km)	722 (457)
Compact Spare Tire	Standard on Liberty Sport and Limited
Full-size Spare Tire with Matching Wheel	Available on Liberty Limited

2010 JEEP® LIBERTY FEATURE AVAILABILITY

LEGEND: S = Standard, O = Optional, P = Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication and is subject to change.

	Sport	Limited
EXTERIOR		
Badges		
4x4 (4WD only)	O	O
Trail Rated (4 WD only)	P	P
Limited	—	S
Colors		
Bright Silver Metallic Clear Coat		
Deep Water Blue Pearl Coat		
Brilliant Black Crystal Pearl Coat		
Inferno Red Crystal Pearl Coat		
Stone White Clear Coat		
Light Sandstone Metallic		
Natural Green Pearl Coat (late availability)		
Dark Charcoal Pearl Coat (late availability)	O	O
Fascias—Front and Rear	S	S
Body-color	S	—
Body-color with bright accents	—	S
Fascias—Body-color rear	S	S
Fender Flares—Body-color	S	S
Fog Lamps—Halogen (included with Popular Equipment Group)	P	S
Glass		
Liftgate, flipper	S	S
Solar Control Glass	S	—
Sunscreen, deep-tinted	P	S
Windshield, tinted	S	S
Grille		
Body-color	S	—
Chromed	—	S
Headlamps—Halogen, round, with parade mode and delay off	S	S
License Plate Brow		
Black mold-in color	S	—
Chromed	—	S
Mirrors		
Dual, power, heated, fold-away	S	S
Molding		
Body-side, Black mold-in color	S	—
Body-side, chromed	—	S
Rear window wiper/washer	S	S
Roof Rails—Side rails (cross bars available through Mopar)		
Black	O	—
Bright		S
Sun Roof—Power tilt-and-slide with solar-tinted glass and express-open feature	O	O
Sky Slider™—Full-open roof system	O	O

2010 JEEP® LIBERTY FEATURE AVAILABILITY

	Sport	Limited
INTERIOR		
Air Filtration	S	S
Air Conditioning	S	S
Assist Handles	S	S
Passenger-side instrument panel-mounted grab handle and assist handles for rear outboard seating positions	S	—
Leather wrapped passenger-side instrument panel mounted grab handles and assist handles for rear outboard seating positions	—	S
Auto Headlamps	S	S
Cargo Area—Tie-down loops (four) recessed in floor	S	S
Cargo-Load Floor, Reversible with 4-inch deep waterproof tray	S	S
Carpeted passenger and cargo floor	S	S
Climate Control		
Air conditioning, manual temperature control	S	S
Heater, with instrument panel ventilation	S	S
Automatic Temperature Control	—	P
Consoles		
Full-length center floor console with dual front cup holders, armrest and large storage bin with removable top tray, and CD/DVD provisions	S	S
Center console—Leather wrapped armrest	—	S
Cover—Cargo compartment	P	S
Defroster—Rear window, electric	S	S
Door Locks—Speed-sensitive, Power	S	S
Floor Carpet	S	S
Floor Mats	S	S
Fuel-saver indicator		
ECO Mode in odometer	S	—
ECO on/off in EVIC	—	S
HomeLink universal transceiver	—	S
Instrument Cluster		
Electronic Vehicle Information Center (EVIC)	—	S
Tachometer	S	S
Temperature, compass	P	S
Interior Colors		
Dark Slate Gray	0	0
Dark Pebble Beige/Pastel Pebble Beige	0	0
Interior Décor		
Satin silver shifter and center-stack bezels	—	S
Interior Lighting		
Illuminated entry	S	S
Map/dome reading lamps	S	S
Second-row dome lamps incorporated into grab handles	S	S
Cargo compartment	S	S
Courtesy lamps	S	S
Memory Package—Driver's seat position, radio settings and exterior mirror position	—	S

2010 JEEP® LIBERTY FEATURE AVAILABILITY

	Sport	Limited
Mirror—Rearview		
Day/night	S	—
Auto-dimming	—	S
Mirror—Vision vanity		
Illuminated	S	S
Power Outlet, 12-volt in center stack	S	S
Seats—Front		
Two-tone premium cloth and stain-repel seat fabric cloth low-back reclining front buckets	S	
Front-Passenger, forward fold-flat	S	S
Premium leather low-back front buckets, manual lumbar and driver-side vinyl seatback map pocket	—	S
Seats—Rear—65/35 split-folding rear recline bench	S	S
Seats—Power		
Six-way driver	—	S
Two-way passenger	—	S
Seats—Heated (with leather only)	—	S
Shift Knob		
Vinyl	S	—
Leather-wrapped	—	S
Sound Systems/Navigation/Communication		
AM/FM/MP3 stereo radio with CD player and auxiliary input jack	S	S
Uconnect Navigation	—	0
Satellite Radio with 1-year subscription to SIRIUS Satellite Radio	S	S
Six full-range speakers	S	—
Eight premium Infinity® speakers, subwoofer and 368-watt amplifier	—	S
Steering-wheel-mounted audio controls	—	S
Uconnect Phone	—	S
Speed Control	P	S
Steering Column—Tilt	S	S
Steering Wheel		
Luxury urethane	S	—
Leather-wrapped	—	S
Sun Visors		
Cloth, with pull-out sunshade	S	S
With illuminated vanity mirrors	S	S
Windows		
Windows—Power with driver and passenger one-touch down	S	—
Windows—Power with driver and passenger one-touch up and down	—	S

2010 JEEP® LIBERTY FEATURE AVAILABILITY

	Sport	Limited
POWERTRAIN AND CHASSIS		
Engine		
3.7-liter V-6 engine	S	S
Transmission		
Four-speed automatic	S	S
Axles		
Dana 30 front axle (4WD only)	P	P
Corporate 8.25 rear axle	S	S
Axle Ratio		
3.73:1	S	S
Brakes		
Four-wheel Anti-lock Brake System (ABS) with Brake Assist	S	S
Electronic Stability Control (ESC) with Electronic-roll Mitigation (ERM) and all-speed traction control	S	S
Four-wheel drive systems (4WD models only)		
Command-Trac® NV253 two-speed part-time transfer case	S	S
Selec-Trac® NV256 two-speed full-time transfer case	O	O
Skid Plates (4WD only)		
	P	P
Steering—Power, rack-and-pinion		
	S	S
Suspension—Front		
Independent front suspension with cast-iron lower and forged-steel upper control arms, coil springs, low-pressure gas-charged shock absorbers, jounce bumpers and stabilizer bar	S	S
Suspension—Rear		
Solid axle with five-link rear suspension (upper and lower trailing lower arms and track bar), coil springs, stabilizer bar and low-pressure gas-charged shock absorbers	S	S
Tires		
P225/75R16 Goodyear BSW, all-season	S	—
P235/70R16 Goodyear OWL, all-season	P	—
P235/70R16 Goodyear OWL, all-terrain	O	—
P235/65R17 Goodyear vertical striated band, all-season	—	S
P235/60R18 Goodyear vertical striated band, all-season	—	O
Tires—Spare		
Compact	S	S
Full-size with steel wheel	O/P	O/P
Full-size with matching wheel	—	P
Tow Hooks—Two front; one rear		
	P	P
Wheels		
16-inch Keystone aluminum wheels	S	—
17-inch Victory aluminum wheels	—	S
18-inch Echelon chrome-clad aluminum	—	O

2010 JEEP® LIBERTY FEATURE AVAILABILITY

	Sport	Limited
SAFETY AND SECURITY		
Brake-shift Interlock (with automatic transmission)	S	S
Door Locks		
Child protection, rear	S	S
Enhanced Accident Response System (EARS)	S	S
Remote Keyless Entry	S	S
Restraint Systems		
Air bags		
Advanced multi-stage driver and front-passenger ^(a) with Occupant-classification System (OCS)	S	S
Supplemental side-curtain ^(b)	S	S
Seat belts		
Front: Three-point, height-adjustable with traveling inboard buckles, Constant-force Retractors (CFR) and driver's pretensioner	S	S
Rear: Three-point belts with LATCH (Lower Anchors and Tethers for Children)	S	S
BeltAlert	S	S
Security Alarm	P	S
Sentry Key® engine immobilizer	S	S
Tire-pressure Monitoring (TPM)		
Warning light	S	—
Full display of individual tire pressure	—	S

^(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.

^(b) Always sit properly in the seat with the seat belt fastened. Always observe the passenger air bag indicator lamp to determine if the OCS classification is appropriate. Children 12 and under should always be in a back seat correctly using an infant or child restraint system or the seat belt positioned correctly for the child's age and weight.

PACKAGES / EQUIPMENT GROUPS

Popular Equipment Group—includes roof rails, compass/temperature (in cluster), cargo shade, speed control, deep-tinted glass, fog lamps, P225/75R OWL all-season tires and security alarm	0	—
Premium Wheel Group—includes 18-inch chrome clad aluminum wheels, P235/60 R18 VSB All-Season tires, full-size spare tire and matching wheel, Trail-rated deleted if equipped with 4x4	—	0
Comfort and Convenience Group—includes Automatic temperature control, Park Sense® Rear-Park Assist System and remote start	—	0
Skid Plate Group (must have 4x4)—Includes four skid plates and three tow hooks	0	0
Trailer-tow Group—Class III—Includes heavy-duty engine cooling, power-steering cooler, Class III receiver hitch, seven-pin wiring harness, seven-to four-pin wiring adapter, Trailer-sway Control (TSC) and full-size spare tire and steel wheel	0	0