LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

2007 Dodge Caravan/Grand Caravan CARAVAN FEATURE AVAILABILITY

| | SE | SX |
|--|----|--------|
| EXTERIOR | | |
| Air Dam, Front | S | S |
| Badges | | |
| "Dodge," bright on lower left of liftgate; Ram's head medallion, | | _ |
| center-mounted on front fascia; "Caravan" on liftgate | | S |
| "SXT" on lower right of liftgate | | S |
| Colors | | |
| Bright Silver Metallic, Inferno Red Tinted Pearl Coat, Modern Blue Pearl Coat, Stone White | 0 | 0 |
| Marine Blue Pearl Coat, Brilliant Black Crystal Pearl Coat, Linen | | |
| Gold Metallic, Magnesium Pearl Coat | 0 | 0 |
| Door Handles, Front and Side | | |
| Black | | _ |
| Body color | | S |
| Doors | | |
| Driver and passenger-side sliding doors with fixed glass | S | S |
| Power sliding passenger-side door | | 0 |
| Fascias, Front and Rear | _ | |
| Molded-in color | | _ |
| Body color | | S |
| Glass | 0 | |
| Tinted | | s |
| Sunscreen | 0 | |
| Headlamps—Halogen | | S S |
| Headlamp-off delay (P6)License Plate Brow | Р | 3 |
| Black | S | |
| Body color | | S |
| Mirrors | | J |
| Dual folding | S | |
| Dual folding, power, heated | | S |
| Molding, Bodyside (accent color) | | S |
| Spat (black) | | S |
| Roof Rack, Black | | 0 |
| Scuff Pad—Rear fascia | | S |
| Wipers | | |
| Windshield, variable intermittent | S | S |
| Rear liftgate window, washer and intermittent | | S |
| INTERIOR | | |
| Bezel, Instrument Panel—Black | | _ |
| Graphite Pattern | | S |
| Cargo Net—Located between front bucket seats | S | S |

| Climate Controls | _ | |
|---|--------|--------|
| Air conditioning, front | S | _ S |
| Air conditioning, dual-zone manual temperature control Console | _ | 5 |
| Instrument panel lower open bin with coin holder | S | S |
| Center between front seats, removable; includes underseat non-locking storage | | Ö |
| Overhead with trip computer, reading lamps, compass/temperature | | |
| display, HomeLink [®] garage door opener, storage bin (P3) | _ | Р |
| Defroster—Electric rear window | | S |
| Door Locks—Power (P2) | Ρ | S |
| Floor Covering | | |
| Carpets, passenger and cargo area, 12-ounce | S | S |
| Floor mats—Front, intermediate and rear | S | S |
| Grocery Bag Hooks—Rear seatback | S | S |
| Illuminated Entry (P3) | Р | S |
| Instrument Cluster (white face) | S | S |
| Tachometer | _ | S |
| Lamps | | |
| Front courtesy | | S |
| Rear dome | | S |
| Liftgate flood | | S |
| Overhead ashtray/cup holder (P3) | | P S |
| Mirror, Day/Night RearviewAuto-dimming rearview (P7) | 5 | о Р |
| Pedals—Power adjustable | 0 | 0 |
| Power Outlets, Front and Rear, 12-volt | S | S |
| Seating, Front | J | J |
| Low-back cloth bucket | S | S |
| Power eight-way driver seat (P3) | | P |
| Lumbar, manual driver seat | | S |
| Seating, Intermediate and Rear | | |
| Deluxe intermediate and rear bench | S | _ |
| Intermediate buckets and rear bench | _ | S |
| Intermediate buckets and rear split bench (P3) | _ | Ρ |
| Intermediate buckets and rear split bench with one integrated child seat | _ | 0 |
| Deluxe intermediate bench and rear bench with two integrated child seats | | _ |
| Easy Out® roller seats | S | S |
| Sound/Entertainment Systems (CD players capable of MP3 playback) | | |
| AM/FM stereo radio with CD player | S | _ |
| AM/FM stereo radio with cassette and CD player | 0 | S |
| AM/FM stereo radio with six-disc in-dash CD changer | _ | 0 |
| SIRIUS Satellite Radio | O P | 0 |
| Rear Seat Video System (P1)UConnect® Hands-free Communication System with Bluetooth® technology | Р | P O |
| Speakers | _ | U |
| · | S | |
| FourSix (P1) | | S |
| Speed Control—Electronic with steering wheel-mounted controls (P2) | | S |
| Steering Column—Tilt (P2) | | S |
| Steering Wheel—Luxury | S | S |
| Storage | | |
| Drawer—Under front passenger seat, lockable | S | S |
| Open bin, lower center stack | | S |
| Sun Visors, Cloth with Vanity Mirrors | | S |
| Illuminated vanity mirrors | _ | Р |
| Windows | | |
| Power front (P2) | Р | _ |
| Power front and rear quarter vents | _ | S |
| | | |

POWERTRAIN/CHASSIS 2.4-liter, DOHC, 16-valve I-4 engine and four-speed automatic transaxle ______ S 3.3-liter, V-6 engine and four-speed automatic transaxle_____ Brakes Power front disc/rear drum _____ S Four-wheel anti-lock ______ 0 Engine Block Heater _____ Front-wheel Drive_____ S S Steering—Power rack and pinion______ S S Suspension Normal duty______ S S Tires es Compact spare _____ S 215/70R15 BSW all-season ______ S S 215/65R16 LBL all-season _____ — Wheels/Wheel Covers 15-inch steel wheels with wheel covers______ S S 16-inch aluminum wheels _____ — SAFETY AND SECURITY Air Bags Advanced multi-stage driver and front passenger air bags with Occupant Classification System (OCS)(a)_____ S Driver-side inflatable knee bolster ______ S Supplemental three-row side-curtain air bags(a) ______ O S Brake—Park Interlock (Cannot shift out of Park unless brake pedal is depressed)______ S Bumpers—Front and rear, 5-mph _____ Door Locks—Power (P2) ______ P Headlamp-Off Time Delay (P6) ______ P S Horn—Electric, Dual-note Illuminated Entry System (P6) Lower Anchors and Tethers for CHildren (LATCH) child seat anchor system—Second row S S S Remote Keyless Entry with Sentry Key Engine Immobilizer (P6)______ P Seat Belts(a) Front—Three-point belts with shoulder belt height adjusters, pretensioners, constant force retractors, and driver/passenger BeltAlert _____ S Intermediate—Three-point belts with shoulder belt height adjusters_____ S Rear—Three-point belts, outboard; lap belt, center ______ S Sliding Door Alert Warning _____ S Tire Pressure Monitoring ____ S (a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, the back seat is the safest place for children. **P1** – Entertainment Group #1: Includes second-row overhead seven-inch video screen: six speakers; AM/FM/CD/DVD Video/Audio MP3 radio; and video remote control _____ O **P2** – Popular Equipment Group—SE: Includes speed control, power front windows, power door locks and tilt steering column _____ O P3 – Popular Equipment Group—SXT: Includes overhead console with trip computer, HomeLink garage door opener, eight-way power driver seat, front low-back bucket seats, intermediate bucket seats, rear split bench seat, overhead ashtray/cup holder light, illuminated visor vanity mirrors, 0 P4 – Heavy-Duty Engine Cooling—Includes engine oil cooler, heavy-duty transmission oil cooler, heavy-duty radiator, heavy-duty condenser (SE)______O 0

| P5 – Remote Keyless Entry—Includes Sentry Key engine immobilizer, headlamp- off time delay, illuminated entry P6 – Security Group—Includes security alarm, remote keyless entry, Sentry Key | 0 | _ |
|---|--------|---------------|
| engine immobilizer, headlamp-off time delay, illuminated entry | 0 | |
| P7 – UConnect® Hands-Free Communication System—Includes auto-dimming rearview r | | _ |
| replaces lower instrument panel storage bin with a faceplate trim cover | | 0 |
| Legend: S = Standard O = Optional P = Available within package or group noted in parentheses — = Available as stand alone option or as part of package/group NOTE: The information shown here is preliminary and based on data available at the time of publicat | | ailable O/P = |
| THO TE. THE INFORMATION SHOWN HOLE TO PROMISINARY and based on data available at the time of publicat | | |
| | | |
| GRAND CARAVAN FEATURE AVAILABILITY | | |
| | SE | SXT |
| EXTERIOR | | |
| Air Dam, Front | S | S |
| Badges | | |
| "Dodge," bright on lower left of liftgate; Ram's head medallion, center- | _ | _ |
| mounted on front fascia; "Grand Caravan" on liftgate | S | S |
| "SXT" on lower right of liftgate | _ | S |
| Colors | | |
| Bright Silver Metallic, Inferno Red Tinted Pearl Coat, Modern Blue | _ | _ |
| Pearl Coat, Stone White | 0 | 0 |
| Marine Blue Pearl Coat, Brilliant Black Pearl Coat, Linen Gold Metallic, | _ | |
| Magnesium Pearl Coat | 0 | 0 |
| Door Handles, Front and Side | _ | |
| Black | S | _ |
| Body color | _ | S |
| Doors | _ | |
| Driver and passenger side sliding doors with fixed glass | S | S |
| Driver and passenger side power sliding | _ | S |
| Fascias, Front and Rear | _ | |
| Body color | S | S |
| Fog Lamps | _ | S |
| Glass | C | |
| Tinted | S P | _ |
| Sunscreen (P2) | Р | S |
| Headlamps | c | c |
| HalogenHeadlamp-off delay | S | S S |
| License Plate Brow | _ | 3 |
| DI I | 9 | |
| | _ | S |
| Body colorLiftgate—Power | | 0 |
| Mirrors | | O |
| Dual, folding | S | _ |
| Dual folding, power, heated (P2) | P | S |
| Molding, Bodyside | • | Ü |
| Accent color | S | _ |
| Body color | _ | S |
| Spat (accent color) | S | S |
| Roof Rack, Black | | S |
| Scuff Pad—Rear fascia | S | S |
| Sun Roof—Power | _ | Ö |
| Wipers—Windshield, variable intermittent; liftgate window, intermittent | S | S |
| · · | | |
| INTERIOR Assist Handles - Descender | | c |
| Assist Handles—Passenger | _ | S |

| Bezel, Instrument Panel—Black | S | |
|--|-----|--------|
| Graphite pattern | _ | S |
| Cargo Net(s) | | |
| One front | S | _ |
| One front, two rear | _ | S |
| Climate Controls | | |
| Air conditioning, front | S | _ |
| Air conditioning, three-zone manual temperature control, rear | | |
| air conditioning with heater (P2) | Ρ | S |
| Air conditioning, three-zone automatic temperature control, rear air | | |
| conditioning with heater (P2) | _ | Р |
| Console | | |
| Instrument panel, lower open bin (center stack) | S | S |
| Center between front seats, removable; includes underseat | | |
| non-locking storage (P3) | _ | Р |
| Overhead with trip computer, reading lamps, compass/temperature | | • |
| display, HomeLink garage door opener, storage bin | _ | S |
| Defroster—Electric rear window | | S |
| Door Locks—Power | | S |
| Floor Covering | O | O |
| Carpets, passenger and cargo area, 12-ounce | S | S |
| Floor mats, front, intermediate and rear | | S |
| Grocery Bag Hooks—Rear seatback | | S |
| Illuminated Entry (P6) | | S |
| | | S |
| Instrument Cluster (white face) Tachometer (P2) | | S |
| | Г | 3 |
| Insulation Palma Insulation Crown (P2) | ь | 0 |
| Deluxe Insulation Group (P2) | | S |
| Hood (P2) | Р | S |
| Lamps | _ | |
| Front courtesy/map | | _ |
| Map/dome reading | | S |
| Rear dome | S | _ |
| Liftgate flood | | S |
| Rear courtesy/reading | | S |
| Overhead ashtray/cup holder | _ | S |
| Mirror—Rearview | | |
| Day/night | | S |
| Auto-dimming (P8) | Р | Р |
| Pedals—Power adjustable | 0 | 0 |
| Power Outlets | | |
| Front and rear, 12-volt | S | S |
| Auxiliary, 12-volt | _ | S |
| Seating, Front | | |
| Low-back cloth bucket | S | S |
| Power eight-way driver seat | | S |
| Leather-trimmed bucket seats (P3) | | Р |
| Lumbar, driver manual | _ | S |
| Seating, Intermediate and Rear | | |
| Deluxe intermediate and rear bench | S | _ |
| Deluxe intermediate bench, two integrated child seats, rear Stow 'n Go (60/40 split) | | _ |
| Stow 'n Go fold-in-floor intermediate bucket seats and rear | - | |
| 60/40 split-folding bench seat with fold-in-floor and tailgate | | |
| position feature | 0 | S |
| Sound/Entertainment/Navigation Systems (CD/DVD, | J | J |
| | | |
| DVD-audio, DVD-R and DVD-RW playback) | c | |
| AM/FM stereo radio with CD playerAM/FM stereo radio with cassette, CD player | S | _ S |
| | () | _ |

| AM/FM stereo radio with six-disc in-dash CD/DVD changer | — | 0 |
|--|------|--------|
| AM/FM stereo radio with CD player and GPS navigation | | 0 |
| SIRIUS Satellite Radio | 0 | Ο |
| UConnect® Hands-free Communication System with Bluetooth™ technology | | 0 |
| Speakers | 0 | |
| Four | S | _ |
| Six (P1) | Р | S |
| Infinity® Acoustic 8 [™] speaker system (P3) | | P |
| Speed Control—Electronic with steering wheel-mounted controls | | S S |
| Steering Column—TiltSteering Wheel | ა | 5 |
| Leather-wrapped | | S |
| Luxury | | _ |
| Storage | 0 | |
| Drawer—Under front passenger seat, lockable | S | S |
| Open Bin, Lower Center Stack | | S |
| Underfloor Storage Bins available when the second-row Stow 'n Go | | Ü |
| seats are in the upright position | _ | S |
| Sun Visors | | |
| Driver and passenger vanity mirrors | S | _ |
| Illuminated vanity mirrors | | S |
| Windows | | |
| Power front (P2) | P | S |
| Power front and rear quarter vents | | S |
| | | |
| POWERTRAIN AND CHASSIS | • | |
| 3.3-liter V-6 engine and four-speed automatic transaxle | | _ S |
| 3.8-liter V-6 engine and four-speed automatic transaxle | | 5 |
| Brakes Power four-wheel disc (P7) | D | c |
| | | S S |
| Four-wheel anti-lock Engine Block Heater | | 0 |
| Steering—Power rack and pinion | | S |
| Suspension | 3 | 3 |
| Normal duty | S | S |
| Touring (P4) | | P |
| Load-leveling and height control (P7) | | Р |
| Tires | | • |
| Compact spare | S | S |
| 215/70R15 BSW all-season | | _ |
| 215/65R16 LBL all-season | _ | S |
| Traction Control—Low-speed | | S |
| Wheels/Wheel Covers | | |
| 15-inch steel wheels with wheel covers | S | _ |
| 16-inch aluminum wheels | | S |
| | | |
| SAFETY AND SECURITY | | |
| Air Bags | | |
| Advanced multi-stage front (driver and passenger)(b) with occupant | | |
| classification system | S | S |
| Driver-side inflatable knee blocker | S | S |
| Supplemental three-row side-curtain air bags(a)(c) | | |
| (not available with power sun roof) | | 0 |
| Brake-Park Interlock | | S |
| Bumpers—Front and rear, 5-mph | S | S |
| Lower Anchors and Tethers for CHildren (LATCH) | _ | |
| child seat anchor system | | S |
| Door Locks—Power | S | S |

| Headlamp-off Time Delay (P6) | Р | S |
|---|-----------|---------------|
| Horn—Electric, Dual-note | S | S |
| Illuminated Entry System | Р | S |
| ParkSense® Rear Backup System | _ | Р |
| | Р | S |
| Seat belts(a) | | |
| Front—Three-point belts with shoulder belt height adjusters, pretensioners, | • | |
| constant force retractors and driver/passenger BeltAlert | S | S |
| Intermediate—Three-point belts with shoulder belt height adjusters | | S |
| Rear—Three-point belts, outboard; lap belt, center | S | S |
| Sliding Door Alert Warning | | S S |
| Tire Pressure Monitoring SystemTraction Control—Low-speed | | 0 |
| Traction Control—Low-speed | _ | U |
| (a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, the back seat is the safest place for children. (b) Certified to the federal regulation for automotive passenger occupant classification. Children 12 and under should always be in the back seat correctly using an infant or child restraint sy or seat belt positioned correctly for the child's size and age. (c) Always sit properly in the seat with the seat belt fastened. Always observe the passenger air bag determine if the OCS classification is appropriate. Children 12 and under should always be in a back an infant or child restraint system or the seat belt positioned correctly for the child's age and weight. | indicate | |
| PACKAGES | | |
| P1 – Entertainment Group #1—Includes second-row overhead seven-inch video screen; | | |
| six speakers; AM/FM/CD/DVD Video/Audio MP3 radio; and video remote control | 0 | _ |
| P2 – Popular Equipment Group II—Includes three-zone manual temperature | | |
| control, rear air conditioning with heater, 160-amp alternator, | | |
| sunscreen glass, tachometer, deluxe insulation group and hood insulation | 0 | |
| P3 – Leather Interior Group—Includes leather-trimmed bucket seats, six-way | | |
| power front passenger seat, heated front seats, three-zone automatic | | |
| temperature control, air filtering, removable front center console, | | |
| Electronic Vehicle Information Center, power liftgate, Infinity® speaker system | _ | 0 |
| P4 – Premium Group—Includes three-zone automatic temperature control, air | | |
| filtering, overhead rail system with storage bins (delete credit when | | |
| power sun roof is ordered), power adjustable pedals, electronic | | |
| vehicle information center, power liftgate, rear park assist, security | | |
| alarm, touring suspension | _ | 0 |
| P5 _ Rear Seat Video System—Includes second-row overhead seven-inch | | |
| video screen, wireless infrared headphones, video remote control, | | |
| overhead rail system with storage bins (when power sun | | |
| roof is ordered) | _ | 0 |
| P6 _ Security Group—Includes security alarm, remote keyless entry | | |
| Sentry Key engine immobilizer, headlamp-off time delay, | | |
| illuminated entry | 0 | _ |
| P7 _ Trailer Tow Prep Group—Includes 160-amp alternator, 600-amp battery, | | |
| engine oil cooler, heavy-duty transmission oil cooler, heavy-duty | | |
| engine cooling, load leveling and height control, heavy-duty radiator, | | |
| wiring harness, rear stabilizer bar | _ | 0 |
| P8 _ UConnect® Hands-free Communication System—Includes auto-dimming | | |
| rearview mirror; replaces lower instrument panel storage bin with a | | |
| faceplate trim cover | _ | 0 |
| Legend: S = Standard O = Optional P = Available within package or group noted in parentheses — = | Not s | roilable O/D |
| Legena. 5 - Standard C = Optional F = Available Within package of group noted in parentneses — = | - INUL dV | aliable U/F = |

 $\label{eq:conditional} \begin{tabular}{ll} Legend: S = Standard O = Optional P = Available within package or group noted in parentheses — = Not available O/P = Available as stand alone option or as part of package/group) \\ \end{tabular}$

NOTE: The information shown here is preliminary and based on data available at the time of publication.

SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.

| GENERAL INFORMATION | |
|--|---|
| Body Style | Multipurpose vehicle |
| Assembly Plants | Windsor, Ontario, Canada and St. Louis, Missouri |
| EPA Vehicle Class | Multipurpose vehicle |
| ENGINE: 2.4-LITER, DOHC, 16-VALVE SM | MPI I-4 |
| Availability | Std.—Caravan SE |
| , | Inline with balance shafts, liquid-cooled |
| Displacement | |
| Bore x Stroke | |
| Valve System | DOHC, 16 valves, stamped-steel rocker arms with roller |
| , | followers, hydraulic lash adjusters |
| Fuel Injection | Sequential multi-port, electronic |
| | Cast-iron block, cast-iron bedplate, aluminum alloy head |
| Compression Ratio | 9.4:1 |
| Power (SAE net) | 150 bhp (112 kW) @ 5,100 rpm (61.8 bhp/L) |
| | 165 lbft. (226 N•m) @ 4,000 rpm |
| Max. Engine Speed | 6,250 rpm |
| Fuel Requirement | Unleaded regular, 87 octane (R+M)/2 |
| | 4.5 qt. (4.25L) plus filter |
| Coolant Capacity | 11.35 qt. (10.74L)Three-way catalytic converter, heated oxygen sensors |
| Emission Controls | Three-way catalytic converter, heated oxygen sensors |
| | and internal engine features(a) |
| Max. Gross Trailer Weight | 1,000 lbs. (450 kg) |
| | wy)20/26 |
| | 3.91 |
| Overall Top Gear | 2.69 |
| ENGINE: 3.3-LITER, OHV, 12-VALVE SMF | PI V-6 |
| Availability | Std.—Caravan SXT, Grand Caravan SE |
| | Six-cylinder, 60° V-type, liquid-cooled |
| Displacement | 201.5 cu. in. (3301 cu. cm) |
| Bore x Stroke | |
| | OHV, 12 valves, roller followers, hydraulic lifters |
| Fuel Injection | Sequential, multi-port, electronic |
| | Cast-iron block, aluminum alloy heads |
| Compression Ratio | |
| | 170 bhp (134 kW) @ 5,000 rpm (54.5 bhp/L) |
| | 200 lbft. (285 N•m) @ 4,000 rpm |
| Max. Engine Speed | |
| Fuel Recommendation | |
| Oil Capacity | 4 qt. (3.8L) plus filter 36 qt. (12.64L)—std.; 16.28 qt. (15.4L)—with rear heater |
| Coolant Capacity 13. | 36 qt. (12.64L)—std.; 16.28 qt. (15.4L)—with rear neater |
| Emission Controls I nree-way cata | alytic converter, heated oxygen sensors, electronic EGR, |
| May Cross Trailer Weight | and internal engine features(a) |
| Max. Gross Trailer Weight | 2,000 lbs. (900 kg)—std.; 3,600 lbs. (1724 kg)— |
| Father to de FDA Front Farmer of (Oite/Ith | with optional Trailer Preparation Group |
| Estimated EPA Fuel Economy mpg (City/H) | wy)19/26 |
| ENGINE: 3.8-LITER, OHV, 12-VALVE SMF | |
| Availability | Six-cylinder, 60° V-type, liquid-cooled |
| Displacement | |
| Bore x Stroke | |
| Valve System | OHV, 12 valves, roller followers, hydraulic lifters |
| | Orro, 12 valves, folier followers, riyuradiic littersSequential, multi-port, electronic |
| Construction | |
| | Sact its.1 blook, alaminam andy floads |

| 9.6:1 53 kW) @ 5,200 rpm (54.5 bhp/L |
|--|
| |
| 235 lbft. (325 N•m) @ 4,000 rpm |
| 5,600 rpm |
| eaded regular, 87 octane (R+M)/2 |
| 4 qt. (3.8L) plus filte |
| 6.28 qt. (15.4L)—with rear heate |
| l oxygen sensors, electronic EGR |
| and internal engine features(a) |
|) kg)—std.; 3,800 lbs. (1724 kg)— |
| nal Trailer Tow Preparation Group |
| 18/25 |
| on requirements. |
| |
| Std.—Al |
| Sid.—Ai nically modulated converter clutch |
| meany modulated convener clutch |
| 0.04 |
| 2.84 |
| 1.57 |
| 1 |
| 0.69 |
| —3.3L engine; 3.43—3.8L engine |
| —3.3L engine; 2.37—3.8L engine |
| |
| ncluded with rear air conditioning |
| ed seats and/or Trailer Tow group |
| :u seals and/or Trailer Tow group .; included with Trailer Tow group |
| |
| —std. with 3.3L and 3.8L engines |
| |
| |
| |
| 113.3 (2878 |
| |
| 63.0 (1600) |
| 63.0 (1600 64.0 (1626 |
| 63.0 (1600 64.0 (1626 189.3 (4808 |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 |
| 63.0 (1600) 64.0 (1626) 189.3 (4808) 78.6 (1997) 68.9 (1749) 5.6 (142) |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m 0.38 20 gal. (75L |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m 0.35 20 gal. (75L |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m 0.35 20 gal. (75L |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m 0.35 20 gal. (75L |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SX 31.17 sq. ft. (2.90 sq. m 0.38 20 gal. (75L 119.3 (3030 63.0 (1600 64.0 (1626 200.5 (5093) |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m 0.35 20 gal. (75L |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m 0.35 20 gal. (75L 119.3 (3030 63.0 (1600 64.0 (1626 200.5 (5093 78.6 (1997 68.9 (1750 |
| 20 gal. (75L) 119.3 (3030) 63.0 (1600) 64.0 (1626) 200.5 (5093) 78.6 (1997) 68.9 (1750) 5.5 (138) |
| 63.0 (1600) 64.0 (1626) 189.3 (4808) 78.6 (1997) 68.9 (1749) 5.6 (142) 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SXT 31.17 sq. ft. (2.90 sq. m) 0.35 20 gal. (75L) 119.3 (3030) 63.0 (1600) 64.0 (1626) 200.5 (5093) 78.6 (1997) 68.9 (1750) 5.5 (138) 0—SE; 4,339 lbs. (1962 kg)—SXT |
| 63.0 (1600 64.0 (1626 189.3 (4808 78.6 (1997 68.9 (1749 5.6 (142 3,763 lbs. (1707 kg)— SE; 3,921 lbs. (1779 kg)—SXT 58/42—SE; 58/42—SX 31.17 sq. ft. (2.90 sq. m 0.39 20 gal. (75L 119.3 (3030 63.0 (1600 64.0 (1626 200.5 (5093 78.6 (1997 68.9 (1750 |
| r |

| Drag coefficient | 0.35 |
|---|----------------------------|
| Fuel tank capacity | 20 gal. (75L) |
| (a) All dimensions measured at curb weight. | |
| ACCOMMODATIONS | |
| Caravan—Short Wheelbase | |
| Seating Capacity, F/I/R | 2/2/3 |
| Front | |
| Head room | 39.6 (1005) |
| Leg room | , |
| Shoulder room | |
| Hip room | |
| Seat travel | |
| Front volume index | 55.9 cu. ft. (1.65 cu. m) |
| Intermediate | |
| Head room | , , |
| Leg room | |
| Knee clearance | |
| Shoulder room | |
| Hip room | 67.8 (1722) |
| Intermediate volume index | 53.7 cu. ft. (1.52 cu. m) |
| Rear | |
| Head room | |
| Leg room | |
| Knee clearance | |
| Shoulder room | 61.9 (1574) |
| Hip room | 49.0 (1246) |
| Rear volume index | 43.2 cu. ft. (1.19 cu. m) |
| Cargo Volume Indexes | |
| Aft of second row seats | |
| Aft of third row seat | , |
| Seats removed | 129.0 cu. ft. (3.65 cu. m) |
| Grand Caravan—Long Wheelbase | |
| Seating Capacity, F/I/R | 2/2/3 |
| Front | |
| Head room | |
| Leg room | |
| Shoulder room | 62.8 (1598) |
| Hip room | |
| Seat travel | |
| Front volume index | |
| Recliner range | 38° |
| Intermediate | 00.4 (00.4) |
| Head room | |
| Leg room | |
| Knee clearance | |
| Shoulder room | |
| Hip room | |
| Intermediate volume index | 51.5 cu. π. (1.46 cu. m) |
| Rear | 00.0 (070) |
| Head room | |
| Leg room | . , |
| Knee clearance | |
| Shoulder room | |
| Hip room | 49.0 (1244) |

Rear volume index _______41.0 cu. ft. (1.16 cu. m)

_____ 49.0 (1244)

Hip room ____

| Cargo Volume Indexes | |
|---|--|
| Aft of second row seats | 85.9 cu. ft. (2.43 cu. m) |
| Aft of third row seat | 32.5 cu. ft. (0.92 cu. m) |
| Seats stowed (fold-in-the-floor) | 144.2 cu. ft. (4.08 cu. m) |
| BODY | |
| Layout | Transverse front engine, front-wheel drive |
| Construction | |
| | sliding left and right side doors—power available; |
| li | iftgate with temperature-compensated gas props—power available |
| SUSPENSION | |
| | ISO struts with integral gas-charged shock absorbers, coil springs, |
| | ver control arms, link-type stabilizer bar, urethane jounce bumpers, |
| asys | rubber-isolated cast-aluminum crossmember—std. |
| Rear I | Rubber-isolated longitudinal single-leaf springs, tubular beam axle, |
| | track bar and gas-charged shock absorbers—std.; |
| Revised s | spring rates and load-leveling shock absorbers—opt. SE and SXT; |
| rtoviou c | stiffer springs, higher control shock—Trailer Towing Group only |
| | ound opinings, might control ones. Trailer returns croup only |
| STEERING - | |
| Type | Rack-and-pinion, power-assisted |
| Overall Ratio | 17.8:1 |
| | 37.6 ft. (11.5 m)—Caravan; 39.4 ft. (12.0 m)—Grand Caravan |
| Steering Turns (lock-to-lock) | 3.14 |
| Mfr. and modelRevs per mile (km) | 215/65R16 low black-letter all-season Bridgestone Turanza EL42 778 (483) |
| Standard—All | |
| | 215/70R15 black sidewall all-season |
| | Goodyear Integrity |
| Revs per mile (km) | 780 (485) |
| WHEELS | |
| Standard—Caravan SE, Grand Ca | aravan SE |
| Type and material | Stamped-steel |
| Size | 15 x 6.5 |
| Optional -Caravan SE, Grand Ca | |
| Type and material | Cast aluminum |
| Size | 16 x 6.5 |
| Standard—Caravan SXT, Grand (| |
| * * | Cast aluminum |
| Size | 16 x 6.5 |
| BRAKES Standard—Caravan SE Front | |
| | 0 (281 x 28) vented disc with 2.60 (66) single-piston sliding caliper 228.5 sq. in. (1474 sq. cm) |
| Rear | |
| | 9.8 x 2.2 (250 x 55) dual-action drum |
| | 134 sq. in. (864 sq. cm) |
| | 10.62 (270) single-diaphragm vacuum |
| Standard—Caravan SXT; Optiona Front | al—Caravan SE |
| Size and type | 11.1 x 1.10 (281 x 28) vented disc with 2.60 (66) single-piston sliding caliper with ABS |

| Swept area | 228.5 sq. in. (1474 sq. cm) |
|------------------------------------|---|
| Rear | |
| Size and type | 9.8 x 2.2 (250 x 55) dual-action drum with ABS |
| Swept area | 134 sq. in. (864 sq. cm) |
| | 10.62 (270) single-diaphragm vacuum |
| Standard— Grand Caravan SE and SXT | |
| Front | |
| Size and type | 11.1 x 1.10 (281 x 28) vented disc with 2.60 (66) |
| | single-piston sliding caliper with ABS |
| Swept area | 228.5 sq. in. (1474 sq. cm) |
| Rear | |
| Size and type | 11.4 x 0.5 (290 x 12.5) solid disc with 1.65 (42) |
| | single-piston sliding caliper with ABS |
| Swept area | 190.5 sq. in. (1229 sq. cm) |
| | 10.62 (270) single-diaphragm vacuum |